



nexthardware.com

a cura di: **Walter Meister - stoner - 03-04-2009 18:26**

Lian Li external HDD rack mount kits



LINK (<https://www.nexthardware.com/news/ssd-hard-disk-masterizzatori/1092/lian-li-external-hdd-rack-mount-kits.htm>)

Lian Li presenta 4 rack HDD Rack

Lian Li ha presentato quattro soluzioni per hard disk in rack mount.

Costruiti interamente in alluminio sono dotati di uno sportello anteriore, hot swap e un pcb posteriore con un controller RAID della Silicon Image (Sil5744 chipset) con connessione SATA.

Il collegamento esterno avviene via USB 2.0 (480Mb/s) ed e-SATA.

In base al modello ci sono diverse soluzioni RAID:

•



Model: EX-10

1 x 3.5" SATA hot swappable HDD

Plug and Play

1 x 60mm ball bearing fan with washable filter (1500RPM)

HDD mounting with Lian Li patented anti-vibration kit

Interface: USB 2.0 x 1, E-SATA x 1, Dim: 175 x 50 x 215 mm (W,H,D)



Model: EX-20

HDD Type: 3.5" SATA

HDD Amount: 2

Interface: USB 2.0 (480Mb/s), e-SATA (3 Gbps, auto-negotiates to 1.5 Gbps)

Raid Controller: Silicon Image, Sil5744

Raid Mode: BIG / JBOD / RAID-0(FAST) / RAID-1(SAFE, SAFE 33, SAFE 50)

Features: Hot Plug / hot swap

Plug and play functionality

Automatic disk rebuild (when one or more RAID 1(SAFE) volumes are configured)

Independent 8KB FIFO/ Port

No driver, BIOS or software required

No drive reformatting on RAID change

LED states for each HDD



Model: EX-30

HDD Type: 3.5" SATA

HDD Amount: 3

Interface: USB 2.0 (480Mb/s), e-SATA (3 Gbps, auto-negotiates to 1.5 Gbps)

Raid Controller: Silicon Image, Sil5744

Raid Mode: BIG / JBOD+ (DISK 2 & DISK3)RAID-0(FAST) / JBOD+ (DISK 2 & DISK3)RAID-1(SAFE)

Features: Hot Plug / hot swap

Plug and play functionality

Automatic disk rebuild (when one or more RAID 1(SAFE) volumes are configured)

Independent 8KB FIFO/ Port

No driver, BIOS or software required

No drive reformatting on RAID change

LED states for each HDD



Model: EX-50

HDD Type: 3.5" SATA

HDD Amount: 5

Interface: e-SATA (3 Gbps, auto-negotiates to 1.5 Gbps)

Raid Controller: Silicon Image, Sil3726 One-to-five native SATA Port Multiplier

Raid Mode: RAID 0, 1, 5, 10 (Running RAID functions With Silicon Image SIL3531 PCI Express to 2-Port Serial ATA II Host Controller card, included, for PC only)

Features: Hot Plug / hot swap

Plug and play functionality

Independent 8KB FIFO/ Port

140mm cooling fan, 3-speed fan controller : 1200-1000-800RPM

LED states for each HDD